

SPTR4

Taps and splitters



4-output "top-down" horizontal splitter with F connector for TV and Satellite band (**5-2400MHz**).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- DC is allowed to pass between the outputs and the input.

SPTR4		
Code		287306
Outputs		4
Impedence	Ω	75
Insertion loss		
RC 5-40MHz	dB	7
TV 47-862MHz	dB	8
SAT 950-1750MHz	dB	8
SAT 1750-2150MHz	dB	9.5
SAT 2150-2400MHz	dB	10
Outputs Isolation		
RC 5-40MHz	dB	20
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	18
SAT 2150-2400MHz	dB	18

Data sheet



Dimensions and packaging		
Pieces		10
EAN code		8016978094837
Multiple EAN		8016978094844
Packaging dimensions	mm	156 x 128 x 65
Product dimensions	mm	77 x 58 x 25
Packaging weight	kg	0.098
Net Weight	kg	1.017
Weight	kg	1.017