


ICOM

VHF MARINE TRANSCEIVER

IC-M73EURO

Slim, Stylish, Powerful VHF with Professional Features



Last Call Voice Recording*

The last call voice recording function automatically saves the last incoming call for 1 minute. You can also start recording manually. You will not miss an important call.



Active Noise Cancelling Technology*

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. You will hear better and clearer!



Bass Boost Function*

The signal processing technology emphasizes low-pitched sound to provide a rich bass sound for both transmit and receive signals.



700mW Loud Audio



6W RF Output Power



IPX8 Advanced Waterproofing

* Basic version (no voice recorder, no noise canceller and no bass boost function) available for limited markets.

700mW Loud Audio

The IC-M73EURO uses a BTL (bridged load) amplifier that doubles the audio output. Its internal speaker delivers a loud 700mW audio output with clear sound.

6W RF Output Power

The IC-M73EURO's 6 Watts*1 of transmit power will provide extended communication range for the user. A large capacity Lithium-Ion battery allows for 18 hours of operation, under normal conditions*2.

*1 1W for FRG version, *2 Typical operation with 5:5:90 duty ratio.

IPX8 Advanced Waterproofing

The IC-M73EURO continues to offer Icom's best waterproof protection. The radio has been tested to survive after being submersed in 1.5m (4.9ft) depth of water for 30 minutes.

Slim, Hourglass Body Wide Viewing Angle LCD

The IC-M73EURO has a stylish, ergonomic design. A durable and rugged body provides for user-friendly operation and long life. A wide viewing angle, high intensity LCD offers bright, easy to read characters.

Additional features

- AquaQuake™ water draining function
- Dual/Tri-Watch function for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Optional waterproof speaker-microphones, HM-167 and HM-202
- Rapid charger BC-210 supplied
- Auto power save function
- FA-S64V short antenna

SPECIFICATIONS

| GENERAL | | |
|--|--|--------------------|
| Frequency range | Tx | 156.000-161.450MHz |
| | Rx | 156.000-163.425MHz |
| Usable channel groups | INT, USA* channels (* Depending on version) | |
| Type of emission | 16K0G3E (FM) | |
| Current drain (at 7.4V DC) | | |
| Tx 6W output | 1.5A | |
| Rx Max. audio (int SP/Ext SP) | 450mA/250mA | |
| Operating temp. range | -15°C to +55°C | |
| Antenna impedance | 50Ω (SMA) | |
| Dimensions (WxHxD) (projections not included) | 52.5x125x30 mm | |
| Weight (approx.) | 320g (With BP-245N, FA-S64V, MB-103) | |

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.

| TRANSMITTER | |
|--|---|
| Output power (Hi/Mid/Low) | 6W/3W/1W 1/0.5W (FRG version) |
| Max. frequency deviation | ±5.0kHz |
| Frequency stability | ±1.5kHz |
| Spurious emissions | 0.25μW |
| Adjacent channel power | 70dB |
| Audio harmonic distortion | Less than 10% (at 60% dev.) |
| Residual modulation | 40dB |
| RECEIVER | |
| Sensitivity (at 20dB SINAD) | -2dBμ emf typ. |
| Squelch sensitivity | -6dBμ emf typ. (at threshold) |
| Adjacent channel selectivity | 70dB |
| Spurious response | 70dB |
| Intermodulation | 68dB |
| Hum and noise | 40dB |
| Audio output power (at 10% distortion, 8Ω load) | 700mW typ. (Internal SP) 200mW (External SP) |

Applicable U.S. Military Specifications & IP Rating

| Standard | MIL 810G | |
|-------------------|----------|-----------|
| | Method | Procedure |
| Low Pressure | 500.5 | I, II |
| High Temperature | 501.5 | I, II |
| Low Temperature | 502.5 | I, II |
| Temperature Shock | 503.5 | I-C |
| Solar Radiation | 505.5 | I |
| Rain Blowing/Drip | 506.5 | I, III |
| Humidity | 507.5 | II |
| Salt Fog | 509.5 | - |
| Dust Blowing | 510.5 | I |
| Immersion | 512.5 | I |
| Vibration | 514.6 | I |
| Shock | 516.6 | I, IV |

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Applicable IP Rating

| Ingress Protection Standard | |
|-----------------------------|------------------------------|
| Water | IPX8 (Waterproof protection) |

OPTIONS


Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACK



BP-245N Li-Ion 7.4V, 1900mAh (min.), 2000mAh (typ.).

RAPID CHARGER



BC-123SE **BC-210**

Charges the BP-245N in 2.5 hours (approx.).

MULTI-CHARGER



BC-197 **BC-157S**

Charges up to six BP-245N in 2.5 hours (approx.). AD-129 is supplied with the BC-197, depending on version.

Supplied Accessories:



- Cigarette lighter cable, CP-25H* • AC adapter, BC-123SE*
- Rapid charger, BC-210 • Battery pack, BP-245N
- Belt clip, MB-103 • Antenna, FA-S59V or FA-S64V*
- Hand strap

* Not supplied or may differ depending on version.

SPEAKER-MICROPHONES



HM-167 **HM-202**

BELT CLIPS




MB-86 **MB-103**

LEATHER BELT HANGERS



MB-96N **MB-96F**

CIGARETTE LIGHTER CABLE & DC POWER CABLES



CP-25H For use with BC-210

OPC-515L For use with BC-210

OPC-656 For use with BC-197

ANTENNAS



FA-S59V (Left) 150mm

FA-S64V (Right) 115mm

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. AQUAQUAKE is a trademark of Icom Inc. (Japan) in the United States. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world **Count on us!**

Icom America Inc.
2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom Canada
Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom Brazil
Rua Pernambuco, 353 - Sala 901
Belo Horizonte, M.G.
30130-150, Brazil
Phone : +55 (31) 3582 8847
Fax : +55 (31) 3582 8987
E-mail : sales@icombrasil.com

Icom (Europe) GmbH
Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone : +49 (6196) 76685-0
Fax : +49 (6196) 76685-50
E-mail : info@icom-europe.com
URL : <http://www.icomeurope.com>

Icom Spain S.L.
Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska
81-850 Sopot, ul. 3 Maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolska@icompolska.com.pl
URL : <http://www.icompolska.com.pl>

Icom (UK) Ltd.
Blacksole House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone : +44 (0) 1227 741741
Fax : +44 (0) 1227 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Icom France s.a.s.
Zac de la Plaine,
1 Rue Bréjondez des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom New Zealand
146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer: