











Product Data Sheet

Magnetic GPS Antenna



GPS

Magnetic Mount Antenna




GPSME

Excellent performance
Active GPS element
Magnetic fixing


However often you use your GPS system the GPSME can help. If you are an occasional user, then you can enjoy the convenience and flexibility of a magnetic system that can be fitted, removed and re-positioned as many times as you want.

If you are a regular user, then the tough magnet in the GPSME will hold it securely in place, ensuring that you get the best GPS coverage all the time.



Magnetic Mount Antenna

E-Plane (GPS)



Part No.		
		GPSME-6SP
Electrical Data		
Frequency Range (MHz)		1575
VSWR		<2.0:1 @ 1575MHz ± 4MHz
LNA Gain		26dB
Polarisation		Right Hand Circular
Operating Voltage		3 - 7V DC (fed via coax)
Current (Typical)		14mA
Impedance		50Ω
Mechanical Data		
Dimensions (mm)	Length	48.6
	Height	15.7
	Width	39.2
Operating Temp (°C)		-40° / +80°C
Material		Engineering plastic
Colour		Black
Mounting Data		
Fixing		Magnetic mount
Termination Data		
Туре		RG174
Thickness (mm)		3
Length (m)		6
Termination		SMA Plug†

Panorama Antennas Ltd

Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444 F: +44 (0)20 8877 4477

E: sales@panorama-antennas.com www.panorama-antennas.com

