





- > ECE R65 APPROVED <
- > LOW CONSUMPTION <
- > EXCELLENT OPTICAL PERFORMANCE <
- > SELECTABLE FLASH PATTERNS <



GEKO LED

LED windshield warning light developed with 6 high power LED and integrated electronic. Anti-glare protection.

It is possible to direct the light emission depending on vehicle type.

Selectable flash patterns (cruise light available).

Polycarbonate dome and ABS housing. Installation by means of dual lock velcro strip.

KEY CHARACTERISTICS

VOLTAGE
12/24V DC

LIGHT EFFECT
Selectable flash patterns

LIGHT INTENSITY
According to ECE R65

PROTECTION GRADE
IP55

OPERATING TEMPERATURE
-40/+65 °C


MECHANICAL FEATURES

Unbreakable polycarbonate dome and ABS housing

OPTICAL FEATURES

Optical group made up of 6 very bright LED. Selectable flash patterns (cruise light available)

DRAWINGS, DIMENSIONS AND WEIGHT



GEKO LED



GEKO LED | PART NO

GEKO LED
(WINDSHIELD WARNING LIGHT)

12/24V



GEKO LED

72990

72989

CERTIFICATIONS



HOMOLOGATION NUMBERS

GEKO LED
(WINDSHIELD WARNING LIGHT)

ECE R65 XA1 E8	00 1113	A
ECE R65 XR1 E8	00 1112	F
EMC 2006/28/CE e8	03 0105 (12/24V)	