

A500 Series Siren

Compact, cost-effective and easy-to-use siren



FEATURES

- Up to 24 tones available: Wail, Yelp, Piercer, HiLo, SUPER HiLo, Alert, Horn and more
- Designed with widely spaced buttons to reduce accidental activation
- Built-in protection against over/under voltage, short circuit and reverse polarity
- Combine our 8Ω siren option with the Magnum H Lightbar or EA50 Speaker for more flexible installation options

SPECIFICATIONS

10-30 Vdc	-100W	-200W	-40 +65 C°	ECE R10	SAE J1849
-----------	-------	-------	------------------	------------	--------------

Operating Current	9.5 amps @ 13.6 Vdc (100W), 19 amps @ 13.6 Vdc (200W)
Siren Frequency Range	500Hz to 2000Hz
PA Audio Frequency Range	300Hz to 10,000Hz
Speaker Impedance	<i>ETSAA501</i> - 1x100W speaker at 11Ω <i>ETSAA502</i> - 2x100W speakers at 11Ω <i>ETSAA503</i> - 1x100W speaker at 8Ω or 2x50w speakers at 4Ω
Lighting Outputs	3x 8 amp outputs, 6x 0.2 amp outputs
Dimensions	Control Unit: 154mm L x 48mm H x 182mm D Remote: 63.5mm L x 25mm H x 127mm D

PART NUMBER

ETSAA501	A500 Series Siren 100W
ETSAA502	A500 Series Siren 200W
ETSAA503	A500 Series Siren 100W 8 Ohm