

GHST

Deck/Grille Mounts



Black Housing, Permanent Mount



White Housing, Single Edge Mount

Single Multi-Mount

Black Housing, 10-16 Vdc

White Housing, 10-16 Vdc

Black Housing, 10-30 Vdc

White Housing, 10-30 Vdc

Black Housing, 10-16 Vdc, ECE 65/EMC Certified

White Housing, 10-16 Vdc, ECE 65/EMC Certified

Black Housing, Xylex Lens (amber blue or red)

White Housing, Xylex Lens (amber blue or red)

Includes three mounting options: Permanent, Single Edge and 3M Adhesive Mount

#EGHST1(x)-12

#EGHST1(x)W-12

#EGHST1(x)

#EGHST1(x)W

#EGHSTE1(x)B

#EGHSTE1(x)W

#EGHSTE1(x)B-EU

#EGHSTE1(x)W-EU

Single Stop/Tail Multi Mount

Black Housing, 10-16 Vdc

White Housing, 10-16 Vdc, Red LEDs

Includes two mounting options: Permanent and 3M Adhesive Mount

#EGHSTTR

#EGHSTTRW

Single Spot Mount

Black Housing, 10-30 Vdc, White LEDs

White Housing, 10-30 Vdc, White LEDs

#EGHSTS1W

#EGHSTS1WW

Dual Multi-Mount

Black Housing, 10-16 Vdc

White Housing, 10-16 Vdc

Black Housing, 10-30 Vdc

White Housing, 10-30 Vdc

Includes three mounting options: Permanent, Dual Edge and 3M Adhesive Mount

#EGHDT1(xx)-12

#EGHDT1(xx)W-12

#EGHDT1(xx)

#EGHDT1(xx)W



Rock Bracket

Warning, 10-16 Vdc

Warning, 10-30 Vdc

Stop/Tail, 10-30 Vdc

Spot, 10-30 Vdc

#EGHST3(x)-12

#EGHST3(x)

#EGHSTT3R

#EGHSTS3W

Replace (x) or (xx) in the Order Number for Color Selection

Solid Colors: A= B= G= R= W=
 Split Colors: D= E= F= G= H= J= K= L= M= N= P=

Features

- > Sleek, narrow surface mount light, fits almost anywhere
- > Premium optics offer optimal power and brightness
- > Red Stop/Tail model is a low power, steady-on red running light once brake is applied, light flashes 5 times and remains on at full power while brake is activated
- > Includes 18" of 3-wire cable
- > Rock light offers an anti-crush, super duty bracket for the most demanding applications and environments
- > Extreme duty rock bracket offers up to 30 degrees of light head adjustability to angle light

GHØST

Deck/Grille Mounts

[continued]

Single/Dual Multi and Single Stop/Tail Mounting Options



Single Edge

Dual Edge

Permanent

3M Adhesive

Technical Specifications

FLASH PATTERNS	33 flash patterns
LIGHT SYNC	4
LED COUNT	6 LEDs
INPUT VOLTAGE	10-16 Vdc or 10-30 Vdc
CURRENT DRAW	<.75 Amps (flash pattern dependent)
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Single/Stop Tail: 5.7" (14 cm) L x 1.06" (2.7 cm) H x 1.8" (4.6 cm) D Dual Stacked: 5.4" (14 cm) L x 2.4" (6.1 cm) H x 1" (2.5 cm) D
MOUNTING	Multi: 4" (10 cm) L x 0.9" (2.3 cm) H x 1.8" (4.6 cm) D Rock: 4.8" (12 cm) L x 2" (5.1 cm) H x 1.6" (4.1 cm) D
CERTIFICATIONS	SAE J595, Class 1 certified; CA Title 13: Article 22 compliant; EMC certified, 72/245/EEC and ECE 65, Category X, Class 1 certified
WARRANTY	Five-year



ACCESSORIES

single deck/grille bracket

Light not included.

- a. Front Single Deck/Grille Bracket, 2015 Chevy Tahoe **#PGHSTDGSB-TH**
(includes both passenger and driver sides)

