

# GHØST

## Surface Mounts



Black Housing

### Single

Black Housing, 10-16 Vdc  
Chrome Housing, 10-16 Vdc  
White Housing, 10-16 Vdc

Black Housing, 10-30 Vdc  
Chrome Housing, 10-30 Vdc  
White Housing, 10-30 Vdc

Black Housing, 10-16 Vdc, ECE 65 Certified  
Chrome Housing, 10-16 Vdc, ECE 65 Certified  
White Housing, 10-16 Vdc, ECE 65 Certified

Xylex Lens; amber, blue and red on all housing colors

Black Housing, 10-30 Vdc, ECE R65/EMC Certified  
Chrome Housing, 10-30 Vdc, ECE R65/EMC Certified  
White Housing, 10-30 Vdc, ECE R65/EMC Certified

Amber, blue and red on all housing colors

#EGHST2(x)-12  
#EGHST2(x)C-12  
#EGHST2(x)W-12

#EGHST2(x)  
#EGHST2(x)C  
#EGHST2(x)W

#EGHSTE2(x)B-EU  
#EGHSTE2(x)C-EU  
#EGHSTE2(x)W-EU

#EGHSTE2(x)B  
#EGHSTE2(x)C  
#EGHSTE2(x)W

### Single Stop/Tail

Black Housing, 10-30 Vdc, Red LEDs  
Black Housing, 10-30 Vdc, Amber LEDs  
Chrome Housing, 10-30 Vdc, Red LEDs  
White Housing, 10-30 Vdc, Red LEDs  
White Housing, 10-30 Vdc, Blue LEDs

#EGHSTT2RB  
#EGHSTT2AB  
#EGHSTT2RC  
#EGHSTT2RW  
#EGHSTT2BW

### Single Spot

Black Housing, 10-30 Vdc, White LEDs  
Chrome Housing, 10-30 Vdc, White LEDs  
White Housing, 10-30 Vdc, White LEDs

#EGHSTS2W  
#EGHSTS2WC  
#EGHSTS2WW

### Dual Stacked

Black Housing, 10-16 Vdc  
Chrome Housing, 10-16 Vdc  
White Housing, 10-16 Vdc

Black Housing, 10-30 Vdc  
Chrome Housing, 10-30 Vdc  
White Housing, 10-30 Vdc

#EGHST6(x)B-12  
#EGHST6(x)C-12  
#EGHST6(x)W-12

#EGHST6(x)B  
#EGHST6(x)C  
#EGHST6(x)W



Black Housing

## Features

- > Sleek, narrow surface mount light, fits almost anywhere
- > Premium optics offer optimal power and brightness
- > Includes rubber mounting gasket and mounting hardware with 3-wire cable




Chrome Housing



White Housing

Replace (x) in the Order Number for Color Selection

Solid Colors: A=  B=  G=  R=  W=   
 Dual/Split Colors: A=  B=  D=  E=  F=  G=  H=  J=  K=  L=  M=  N=  P=  R=  W= 

Technical Specifications

FLASH PATTERNS	33 flash patterns
LIGHT SYNC	4 single and 2 dual-stacked
LED COUNT	Single: 6 LEDs Dual Stacked: 12 LEDs (6 per module)
INPUT VOLTAGE	10-16 Vdc or 10-30 Vdc
CURRENT DRAW	Single: 0.75 Amps (flash pattern dependent) Dual Stacked: > 1.5 Amps
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Single/Stop Tail: 5.7" (14 cm) L x 1.06" (2.7 cm) H x 1.8" (4.6 cm) D Dual Stacked: 5.4" (14 cm) L x 2.4" (6.1 cm) H x 1" (2.5 cm) D
MOUNTING	Single: On 4.9" (12.4 cm) centers Dual Stacked: 4.85" (12 cm) centers
CERTIFICATIONS	SAE J595, Class 1 certified; Article 22, CA Title 13 compliant; Two, ECE 65 certified and 72/245/EEC, EMC certified
WARRANTY	Five-year



ACCESSORIES

single surface mount brackets

Light not included.

- a. Side Mirror Grommet (pair), Ford Interceptor Sedan, 2013+ **#PGHSTSMMPFI**
- b. Behind the grille installation, includes driver and passenger sides, Chevy Tahoe, 2015 **#PNFSLDGSB-TH**
- c. Single Surface Mount Vertical License Plate **#PNFSLBRK2LPV**

