



# 7000 Mini LED Lightbar



**EPL7000**

### Clear Dome

- Magnetic with Cig Plug
- Magnetic with Cig Plug
- Standard Permanent (shown)
- Standard Permanent
- High Permanent

- EPL7M+(x)C**
- EPL7M+(y)C**
- EPL7PD(x)C**
- EPL7PD(y)C**
- EPL7HD(x)C**

### Clear Dome (25 foot cable)

- Standard Permanent
- Standard Permanent
- High Permanent

- EPL7PF(x)C**
- EPL7PF(y)C**
- EPL7HF(x)C**

Replace (x) or (y) in the Order Number for Standard Color Selection

Solid Colors (x): A = ● B = ● R = ● W = ○

Split Colors (x): D = ●○ E = ●○ F = ●○ J = ●● K = ●● M = ●●

Solid Color (y): G = ●

Split Colors (y): H = ●○ L = ●● N = ●● P = ●●

### Configurable Options ●●●●○

To order configured products, contact your sales representative or customer service department.



**EPL7000**

### Amber Dome, Amber LEDs

- Magnetic with Cigar Plug (shown)
- Standard Permanent
- High Height Permanent

- EPL7M+AA**
- EPL7PDAA**
- EPL7HDAA**

### Amber Dome, Amber LEDs (25 foot cable)

- Standard Permanent
- High Height Permanent

- EPL7PFAA**
- EPL7HFAA**

## Features

- Magnetic mount has cig plug with 2-button switch panel (on, off and flash pattern advance)
  - Red LED indicator light and 10' cord length
  - 4 extra strong magnets each with an 85 pound pull each to prevent the lightbar from slipping or moving
- Fusion II Technology optic for a bright, extra wide output
- Non-volatile memory that recalls last flash pattern used

## Technical Specifications

<b>INPUT VOLTAGE RANGE</b>	10-16 Vdc
<b>CURRENT DRAW</b>	2 Amps average @ 12.8 Vdc
<b>LED COUNT</b>	24 LEDs
<b>FLASH PATTERNS</b>	28 flash patterns
<b>OPERATING TEMPERATURE</b>	-40° C to +65° C / -40° F to +149° F
<b>DIMENSIONS</b>	<b>Length:</b> 4 Module: 14.16" (36 cm) <b>Height:</b> 1.90" (4.8 cm) <b>Depth:</b> 8.27" (21 cm)
<b>MOUNTS</b>	Magnetic mount, Permanent mount or High Permanent mount
<b>CERTIFICATIONS</b>	SAE J845 Class 1 certified (blue or red solid color LEDs only)
<b>WARRANTY</b>	Five-year

1.800.338.7337



# 7100 Mini LED Lightbar



**EPL7100**

### Clear Dome Magnetic Mount

Amber LEDs	<b>EPL71M+AC</b>
Amber/White LEDs	<b>EPL71M+FC</b>
Red/Amber LEDs	<b>EPL71M+KC</b>
Blue/Amber LEDs	<b>EPL71M+MC</b>
Green Solid/Split LEDs	<b>EPL71M+(y)C</b>

### Clear Dome Standard Permanent Mount

Amber LEDs	<b>EPL71PDAC</b>
Amber/White LEDs (shown)	<b>EPL71PDFC</b>
Red/Amber LEDs	<b>EPL71PDKC</b>
Blue/Amber LEDs	<b>EPL71PDMC</b>

### Clear Dome High Permanent Mount

Amber LEDs	<b>EPL71HDAC</b>
Amber/White LEDs	<b>EPL71HDFC</b>
Red/Amber LEDs	<b>EPL71HDKC</b>
Blue/Amber LEDs	<b>EPL71HDMC</b>

Replace (y) in the Order Number for Standard Color Selection

Solid Color (y): G = ●

Split Colors (y): H = ●○ L = ●● N = ●● P = ●●



**EPL7100**

### Amber Dome Magnetic Mount

Amber LEDs (shown)	<b>EPL71M+AA</b>
--------------------	------------------

### Amber Dome Standard Permanent Mount

Amber LEDs	<b>EPL7PD+AA</b>
------------	------------------

### Amber Dome High Permanent Mount

Amber LEDs	<b>EPL71HDA A</b>
------------	-------------------

## Features

- Magnetic mount has cig plug with 2-button switch panel (on, off and flash pattern advance)
  - Red LED indicator light and 10' cord length
  - 4 extra strong magnets each with an 85 pound pull each to prevent the lightbar from slipping or moving
- Fusion II Technology optic for a bright, extra wide output
- Non-volatile memory that recalls last flash pattern used

## Technical Specifications

<b>INPUT VOLTAGE RANGE</b>	10-16 Vdc
<b>CURRENT DRAW</b>	2 Amps average @ 12.8 Vdc
<b>LED COUNT</b>	24 LEDs
<b>FLASH PATTERNS</b>	28 flash patterns
<b>OPERATING TEMPERATURE</b>	-40° C to +65° C / -40° F to +149° F
<b>DIMENSIONS</b>	<b>Length:</b> 4 Module: 14.16" (36 cm) <b>Height:</b> 1.90" (4.8 cm) <b>Depth:</b> 8.27" (21 cm)
<b>MOUNTS</b>	Magnetic mount, Permanent mount or High Permanent mount
<b>CERTIFICATIONS</b>	SAE J845 Class 1 certified (amber solid color LEDs only)
<b>WARRANTY</b>	Five-year