

nLINE

Running Light



48" Length Shown

48" Driver, Left Side Wire Exit	ENL148(x)-L
48" Passenger, Right Side Wire Exit	ENL148(x)-R
60" Driver, Left Side Wire Exit	ENL160(x)-L
60" Passenger, Right Side Wire Exit	ENL160(x)-R
72" Driver, Left Side Wire Exit, Red/Blue	ENL172J-L
72" Passenger, Right Side Wire Exit, Red/Blue	ENL172J-R

Replace (x) in the Order Number for Standard Color Selection

Solid Colors: A=● B=● R=●

Dual/Split Color: J=●●

Features

- Light is sold per unit
- Light can be surface mounted to any flat area on any type of vehicle
- Prime applications include rocker panels, push bumpers, tailgates and headache racks
- Distributes exceptional profile visibility to dangerous intersections
- Compact extruded aluminum housing is visually inconspicuous and weather resistant
- 19 inches of wire cable for hard wire installation



Technical Specifications

INPUT VOLTAGE	10-16 Vdc
CURRENT DRAW	0.58 Amps @ 16 Vdc
LIGHT SYNC	6
FLASH PATTERNS	10 flash patterns
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Widths: 36" (91.4 cm); 48" (121.9 cm); 60" (152.4 cm) or 72" (182.9 cm) Depth: .75" (1.9 cm) (all lights)
MOUNTING	Surface mount
WARRANTY	Three-year

1.800.338.7337