

DIGI 14, LTE 700, Ch 21-48 (Color box)

Art. Number 105470



TRIAX UHF LTE 700 Aerials

Disruption free installation from rooftop to outlet.

- Interference protection from LTE 700 & 800 signals
- Quick and easy installation with semi-assembled aerials
- Mechanical filtering for higher gain
- Reliable high-quality aerials secures end-consumer satisfaction
- Corrosion and weather proof dipole housing
- Designed to receive DTT signals in the 470...694 MHz range
- Access to reliable, expert support from TRIAX

Technical Specifications

ORDER INFORMATION

EAN Number 5702661054709

FREQUENCY RANGE

Band UHF
 Channels 21...48
 Frequency range UHF | MHz 470...694 MHz
 LTE protection @ 700Mhz

GAIN

Gain | dBi 13.5 max dBi
 Gain @ 474 MHz (Ch. 21) | dBi 10.9 dBi

LOSS

Rejection @ 788 MHz (Ch. 60) | dB 8.3 dB

ELECTRICAL

Front to back ratio - horizontal | dB 23 dB

MECHANICAL



Technical Specifications

Elements	14
Windload @42 m/s N	54 N
Beamwidth horizontal °	±30 °
Bracketry	Mast bracket - rear
Main material	Aluminium
Packing QTY	1
Product Height mm	67 mm
Product Length mm	1085 mm
Product Width mm	1100 mm
Product Depth mm	125 mm
Packaging Height m	0.075 m
Packaging Width m	1.100 m
Packaging Depth m	0.023 m
Packaging Volume m3	0.019 m3
Net Weight kg	0.884 kg
Tara Weight kg	0.434 kg
Total Weight kg	1.318 kg