

F-compression connector 5.1/6.8 short, 100 pcs.
bag

Art. Number 153224



TRIAx F-compression connector 5.1/6.8 short

Technical Specifications

ORDER INFORMATION

EAN Number 5702661532245

SHIELDING

Shielding @ 1 GHz | dB > 115 dB

CHARACTERISTICS

Cable type KOKA 600, KOKA 80, KOKA 6

Tool 360920

FREQUENCY RANGE

Frequency range | MHz 0.3-3000 MHz

LOSS

Insertion loss (typ.) | dB < 0.01 @ 860-1000 MHz dB

RETURN LOSS

Return Loss | dB -36.0 @ 860-1000 MHz dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL

Temperature - operating | °C -40...100 °C

MECHANICAL



TRIAx

connecting the future

Technical Specifications

Plating	Nitin
Colour	Red
Packing QTY	100
Product Height mm	27 mm
Product Width mm	10 mm
Product Depth mm	10 mm
Packaging Height m	0.190 m
Packaging Width m	0.115 m
Packaging Depth m	0.000 m
Packaging Volume m3	0.000 m3
Net Weight kg	0.008 kg
Tara Weight kg	0.000 kg
Total Weight kg	0.008 kg