



IEC-female/F-female adaptor angled, 100 pcs.
bag

Art. Number 153551



IEC-female to F-female adaptor angled

Technical Specifications

ORDER INFORMATION

EAN Number 5702661535512

SHIELDING

Shielding @ 30-1000 MHz | dB >95 dB

Shielding @ 1000-2000 MHz | dB >85 dB

Shielding @ 2000-3000 MHz | dB >75 dB

FREQUENCY RANGE

Frequency range | MHz 5-1000 MHz

LOSS

Insertion loss (typ.) | dB < 0.36 (@862MHz) dB

RETURN LOSS

Return Loss | dB -18 @862MHz) dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL

Screening Efficiency EN50117 (Class A+)

Temperature - operating | °C -40...100 °C

MECHANICAL

Plating Nickel/Gold inner pin

Packing QTY 100



TRIAx

connecting the future

Technical Specifications

Product Height mm	20 mm
Product Width mm	20 mm
Product Depth mm	8 mm
Packaging Height m	0.210 m
Packaging Width m	0.170 m
Packaging Depth m	0.000 m
Packaging Volume m ³	0.000 m ³
Net Weight kg	0.010 kg
Tara Weight kg	0.000 kg
Total Weight kg	0.010 kg