

IEC-male/F-female adaptor angled, 100 pcs. bag

Art. Number 153550



IEC-male to F-female adaptor angled

### Technical Specifications

#### ORDER INFORMATION

EAN Number 5702661535505

#### SHIELDING

Shielding @ 30-1000 MHz | dB >95 dB

Shielding @ 1000-2000 MHz | dB >85 dB

Shielding @ 2000-3000 MHz | dB >75 dB

#### FREQUENCY RANGE

Frequency range | MHz 5-1000 MHz

#### LOSS

Insertion loss (typ.) | dB < 0.38 (@862MHz) dB

#### RETURN LOSS

Return Loss | dB -17.5 (@862MHz) dB

#### ELECTRICAL

Impedance |  $\Omega$  75  $\Omega$

#### OPERATIONAL

Screening Efficiency EN50117 (Class A+)

Temperature - operating | °C -40...100 °C

#### MECHANICAL

Plating Nickel/Gold inner pin

Packing QTY 100

Product Height | mm 20 mm



# TRIAx

connecting the future

## Technical Specifications

Product Width   mm	20 mm
Product Depth   mm	8 mm
Packaging Height   m	0.210 m
Packaging Width   m	0.170 m
Packaging Depth   m	0.000 m
Packaging Volume   m <sup>3</sup>	0.000 m <sup>3</sup>
Net Weight   kg	0.010 kg
Tara Weight   kg	0.000 kg
Total Weight   kg	0.010 kg