



TRIAX

connecting the future

TDS 65A RAL 7016, singlepack

Art. Number 120500



TRIAX TD Dishes The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
 - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
 - TRIAX's unique cable protection system
 - Every part, every accessory is weatherproofed
 - 2 years corrosion warranty
 - 5 years functionality warranty
- Outstanding performance
 - High gain for an exceptional signal
- Quick and easy installation
 - One-click mounting system
 - Self-locking screw & nuts
- Logistic friendly
 - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

Technical Specifications

ORDER INFORMATION

EAN Number 5702661205002



Technical Specifications

CHARACTERISTICS

F/D ratio	0,62
G/T LNB 0.7 dB/K	16.0 dB/K
X-polarisation dB	≤ -25 dB
Offset angle °	26 °
Elevation range °	0...90 °

FREQUENCY RANGE

Frequency range GHz	10.7...12.75 GHz
-----------------------	------------------

GAIN

Gain @ 11.7 GHz dBi	36 dBi
-----------------------	--------

MECHANICAL

Height (cm) cm	66 cm
Width (cm) cm	60 cm
LNB holder	40
Mast bracket diameter mm	30...60 mm
Reflector type	Offset
Beamwidth °	3.1 °
Main material	Galvanized steel (hot-dip)
Arm Colour	Raw
Colour	RAL 7016 - Anthracite grey
Packing QTY	1
Packaging Height m	0.734 m
Packaging Width m	0.684 m
Packaging Depth m	0.100 m
Packaging Volume m ³	0.050 m ³
Net Weight kg	3.220 kg
Tara Weight kg	1.050 kg
Total Weight kg	4.270 kg