

TDS 65LG RAL 7035, bulk pack

Art. Number 120503



TRIAX TD Dishes The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
 - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
 - TRIAX's unique cable protection system
 - Every part, every accessory is weatherproofed
 - 2 years corrosion warranty
 - 5 years functionality warranty
- Outstanding performance
 - High gain for an exceptional signal
- Quick and easy installation
 - One-click mounting system
 - Self-locking screw & nuts
- Logistic friendly
 - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

Technical Specifications

ORDER INFORMATION

EAN Number

5702661205033



TRIAx

connecting the future

Technical Specifications

CHARACTERISTICS

F/D ratio	0,62
G/T LNB 0.7 dB/K	16.0 dB/K
X-polarisation dB	≤ -25 dB
Offset angle °	26 °
Elevation range °	0...90 °

FREQUENCY RANGE

Frequency range GHz	10.7...12.75 GHz
-----------------------	------------------

GAIN

Gain @ 11.7 GHz dBi	36 dBi
-----------------------	--------

MECHANICAL

Height (cm) cm	66 cm
Width (cm) cm	60 cm
LNB holder	40
Mast bracket diameter mm	30...60 mm
Reflector type	Offset
Beamwidth °	3.1 °
Main material	Galvanized steel (hot-dip)
Arm Colour	Raw
Colour	RAL 7035 - Light grey
Packing QTY	220
Packaging Height m	0.010 m
Packaging Width m	0.600 m
Packaging Depth m	0.660 m
Packaging Volume m3	0.004 m3
Net Weight kg	3.400 kg
Tara Weight kg	0.000 kg
Total Weight kg	3.400 kg