

IFP 224 PSU + Inserter 2 out 24V/200mA

Art. Number 339224



TRIAX power supplies in elegant design.

F-connector on all inputs. Simple and easy installation. The 2 outputs are equipped with auto-terminated F connector meaning that there is no need to terminate an un-used output. Including a power supply / inserter to power a UFO antenna when used in a camping-car and powered from the 12V DC delivered from the camping-car.

- 2 inputs, AC + DC 12V
- Automatic switch from 12 VDC to 230V AC input upon availability
- When connected to 230V AC, delivers 24V DC 200mA
- When connected to camping-car 12V DC, delivers 12V DC 200mA
- 1 x RF F-connector input
- 2 x RF auto-terminated F-connector outputs for 2 x TV sets
- Signal insertion loss: 4dB.
- Quick and easy installation
- Install instruction already available on UFO 150/170 box and manual
- Single packed in compact color retail cardboard box.

Technical Specifications

ORDER INFORMATION

EAN Number 5702663392243

CHARACTERISTICS

FREQUENCY RANGE

Frequency range | MHz 47...862 MHz

LOSS

Through loss | dB 4.0 dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL

DC Supply Voltage | VDC 12 VDC



Technical Specifications

AC Supply voltage VAC	100...240 VAC
PSU output DC voltage VDC	24 (12@inserter) VDC
PSU output max. DC current mA	200 mA

CONNECTORS

Number of inputs	2
Number of outputs	2

MECHANICAL

Packaging Depth m	0.150 m
Packaging Height m	0.070 m
Total Weight kg	0.345 kg
Packaging Width m	0.110 m
Net Weight kg	0.315 kg
Tara Weight kg	0.030 kg
Packaging Volume m3	0.001 m3